

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 3/23/2017 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Trade name : VAPROX® HC Sterilant : PB007, PB028 Product code

SDS No A124

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Product for industrial use only

Use of the substance/mixture : For use only with STERIS V-PRO® Sterilizers

1.2.2. Uses advised against

No additional information available

Details of the supplier of the safety data sheet 1.3.

STERIS Corporation

P. O. Box 147, St. Louis, MO 63166, US

Telephone Number for Information: 1-800-548-4873 (Customer Service-Healthcare Products) US Emergency Telephone No.1-314-535-1395 (STERIS); 1-800-424-9300 (CHEMTREC)

Emergency telephone number

: US Emergency Telephone No.1-314-535-1395 (STERIS); 1-800-424-9300 (CHEMTREC) Emergency number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS classification

Ox. Liq. 2 H272 Acute Tox. 4 (Oral) H302 Acute Tox. 4 (Inhalation:dust,mist) H332 Skin Corr. 1B H314 STOT SE 3 H335 Full text of H-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements-This product is regulated by the US FDA and Health Canada and is exempt from GHS labelling.

Labelling according to GHS

Signal word (GHS)

Hazard pictograms (GHS)





GHS03 GHS05

: Danger

: H272 - May intensify fire; oxidiser Hazard statements (GHS) H302 - Harmful if swallowed

H332 - Harmful if inhaled

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Precautionary statements (GHS)

SDS Ref: A124US 3/23/2017 EN (English) 1/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

smoking

P261- Avoid breathing mist and/or vapours

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P370 + P378 – In case of fire: Use water for extinction

2.3. Other hazards

Risk of decomposition by heat or by contact with incompatible materials.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS Classification
Hydrogen peroxide	(CAS No) 7722-84-1	59	Ox. Liq. 1, H271 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 STOT SE 3, H335

Full text H-phrases: see section 16

First-aid measures after inhalation

First-aid measures after skin contact

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: Never give anything by mouth to an unconscious person. In all cases of doubt, or when

symptoms persist, seek medical attention

: Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Immediately get medical attention

artificial respiration. Immediately get medical attention

: Remove contaminated clothing immediately. Immediately flush skin with plenty of water for at least 15 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated

clothing before reuse

First-aid measures after eye contact : In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes

holding eyelids apart. Immediately get medical attention. Remove contact lenses, if present and

easy to do. Continue rinsing.

First-aid measures after ingestion : If victim completely conscious/alert, give water or milk. Rinse mouth. Do NOT induce vomiting.

Obtain emergency medical attention. Call a POISON CENTER/doctor/physician if you feel

Obtain emergency medical attention. Can a 1 010010 CENTER/doctor/physician if you rec

unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Hydrogen peroxide at these concentrations is a strong oxidant. Causes severe skin burns and eye damage

Symptoms/injuries after inhalation

: Harmful if inhaled. Possible inflammation or irritation of the respiratory tract or pulmonary edema.

Symptoms/injuries after eye contact

: Eye contact with concentrated solutions may cause severe eye damage followed by loss of sight

Symptoms/injuries after ingestion

Swallowing a small guantity of this material will result in serious health hazard. Severe irritation

or burns to the mouth, throat, esophagus, and stomach

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water or water fog

Unsuitable extinguishing media : Do not use foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of

fire

: Hydrogen peroxide at these concentrations is a strong oxidant. On decomposition releases oxygen which may intensify fire. Containers may swell and burst during a fire due to internal pressure caused by heat

3/23/2017 EN (English) SDS Ref: A124US 2/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

Precautionary measures fire

: On heating, there is a risk of bursting due to internal pressure build-up. Cool down the containers exposed to heat with a water spray

Firefighting instructions

: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment

Protective equipment for firefighters

: Use self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection

Other information

Oxygen evolution decomposition may burst sealed containers and accelerate the burning rates of other combustible materials. Damp material in contact with paper, wood, cloth, etc. may cause spontaneous combustion of the organic material

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Ensure adequate ventilation. Do not breathe fumes or vapors. Avoid contact with skin, eyes and clothes. Contain spill if safe to do so

6.1.1. For non-emergency personnel

Protective equipment

: Wear protective gloves and eye/face protection. For further information refer to section 8 : Exposure-controls/personal protection

Emergency procedures

: Contain spill if safe to do so. Evacuate unnecessary personnel

6.1.2. For emergency responders

Protective equipment

: Equip cleanup crew with proper protection

Emergency procedures : Ventilate area

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Spills should be contained and may be cautiously neutralized with sodium metabisulfite or sodium sulfite (1.0 lb of either to 100 ml peroxide), or absorbed on appropriate materials and placed in a container for disposal. Do not use sawdust or cellulose materials as an absorbent. Flush spill site with large quantities of water (20 parts water to 1 part hydrogen peroxide) to a sanitary sewer.

Other information

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in fire

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Read and observe all labeled use instructions.

Hygiene measures

: Take care for general good hygiene and housekeeping. Wash hands thoroughly after handling. Contaminated clothing should be washed thoroughly in order to eliminate a delayed potential fire hazard. Do not eat, drink or smoke when using this product

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Provide adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present. Floors should be impervious, resistant to liquids and easy to clean.

Storage conditions

: Store in a cool, well ventilated place.

Incompatible materials

: Strong alkalis. Strong oxidizing agents. Organic materials. Reducing agents. Metal salts. Alkali metals. Wood. Paper. Copper and its alloys. Metals. Cyanide. Hazardous reactions may occur on contact with certain chemicals. (Refer to the list of incompatible materials section 10: "Stability-Reactivity")

Prohibitions on mixed storage

Special rules on packaging

Keep away from incompatible materialsStore in dry, cool, well-ventilated area

Storage area

: Correctly labelled

3/23/2017 EN (English) SDS Ref: A124US 3/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrogen peroxide (7722-84-1)		
USA - ACGIH	ACGIH TWA (ppm)	1 ppm
USA - NIOSH	NIOSH IDLH (ppm)	75 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m³)	1.4 mg/m³
USA - NIOSH	NIOSH REL (TWA) (ppm)	1 ppm
USA - OSHA	OSHA PEL (TWA) (mg/m³)	1.4 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1 ppm

8.2. Exposure controls

Appropriate engineering controls

: Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Local exhaust ventilation is recommended to maintain vapor level below the threshold limit value (TLV)

Personal protective equipment

: Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Protective clothing. Gloves. Protective goggles. Avoid all unnecessary exposure







Hand protection

: Wear protective gloves. Use gloves constructed of chemical resistant materials such as nitrile, neoprene, rubber, or vinyl if frequent or prolonged contact is expected.

Eye protection

: Wear protective eyewear.

Skin and body protection

: Wear suitable protective clothing. Chemical resistant lab coat and closed toe shoes

Respiratory protection

Other information

: None required for routine use. In emergency situations where established limits are exceeded, it is recommended to use SCBA (Self-Contained Breathing Apparatus)

: Do not eat, drink or smoke during use

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear
Colour : Colourless
Odour : Odourless
Odour threshold : No data available

pH : ≤ 3.5 Relative evaporation rate (butyl acetate=1) : >1

Melting point : No data available

Freezing point : -55°C

Boiling point : 119°C

Flash point : Not flammable

Auto-ignition temperature : Not flammable

Decomposition temperature : > 85°C

Flammability (solid, gas) : Non flammable

Flammability (solid, gas) : Non flammable

Vapour pressure : 14.2 mm Hg @ 30°C

Relative vapour density at 20 °C : No data available

Relative density : No data available

Density : 1.24 g/ml Specific Gravity @ 20°C

3/23/2017 EN (English) SDS Ref: A124US 4/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility : Water: completely soluble

Log Pow : -1.57 @ 20°C

Viscosity, kinematic : No data available

Viscosity, dynamic : 1.079 cP @ 25°C

Explosive properties : Not explosive

Oxidising properties : Oxidizer

Explosive limits : Not explosive

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactive and oxidizing agent.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur. Contamination may cause rapid decomposition, oxygen gas release and dangerous pressures

10.4. Conditions to avoid

Extremely high or low temperatures. Protect from all contamination

10.5. Incompatible materials

Respiratory or skin sensitisation

Cyanides, hexavalent chromium compounds, nitric acid, potassium permanganate, oxidizers, reducers, combustible materials, flammable vapors, alkalies, copper, dirt, dust, iron, heavy metals and their salts and organic materials (especially vinyl monomers)

10.6. Hazardous decomposition products

Contamination may cause rapid decomposition, oxygen gas release and dangerous pressures

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful if inhaled.

VAPROX® HC Sterilant	
ATE (oral)	500.000 mg/kg bodyweight
ATE (dust,mist)	1.500 mg/l/4h

Hydrogen peroxide (7722-84-1)	
LD50 oral rat	801 mg/kg
LD50 dermal rat	4060 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	2 g/m³ (Exposure time: 4 h)
ATE (oral)	801.000 mg/kg bodyweight
ATE (dermal)	2000.000 mg/kg bodyweight
ATE (gases)	4500.000 ppmv/4h
ATE (vapours)	2.000 mg/l/4h
ATE (dust,mist)	2.000 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage

pH: <= 3.5

Serious eye damage/irritation : Serious eye damage, category 1, implicit

pH: <= 3.5 : Not a sensitizer

Germ cell mutagenicity : This product is not recognized as mutagenic by Research Agencies.

In vivo tests did not show mutagenic effects.

3/23/2017 EN (English) SDS Ref: A124US 5/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : IARC, NTP and OSHA do not list this product or its ingredients as carcinogens. ACGIH lists

hydrogen peroxide as a "Confirmed Animal Carcinogen with Unknown Relevance to Humans"

A3.

Reproductive toxicity : Not classified

Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : Eyes. Respiratory System. Skin.

Specific target organ toxicity (repeated

exposure)

: Not classified

Based on available data, the classification criteria are not met

Aspiration hazard : Not classified

Based on available data, the classification criteria are not met

Potential Adverse human health effects and

symptoms

: Harmful if swallowed. Harmful to eyes and skin.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects

Hydrogen peroxide (7722-84-1)	
LC50 fishes 1	16.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	7.7 mg/l (Exposure time: 24 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	2.5 mg/l (Exposure time: 72 h - Species: Chlorella vulgaris)
LC50 fish 2	18 - 56 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [Static])
EC50 Daphnia 2	18 - 32 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and degradability

VAPROX® HC Sterilant	
Persistence and degradability	Hydrogen peroxide in the aquatic environment is subject to various reduction or oxidation processes and decomposes into water and oxygen. Hydrogen peroxide half-life in freshwater ranged from 8 hours to 20 days, in air from 10-20 hours and in soils from minutes to hours depending upon microbiological activity and metal contaminants.

12.3. Bioaccumulative potential

VAPROX® HC Sterilant	
Bioaccumulative potential Not established	
Hydrogen peroxide (7722-84-1)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in soil

Will likely be mobile in the environment due to its water solubility.

12.5. Results of PBT and vPvB assessment

This product is not considered to be persistent, bioaccumulating nor toxic (PBT).

12.6. Other adverse effects

Decomposes into oxygen and water.

No adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Empty cartridges may be disposed in normal trash. Expired cartridges should be disposed of according to local policies for hazardous materials. For additional guidance, contact the State

Water Board or the Regional Office of the EPA..

Additional information : Not applicable

Ecology - waste materials : Decomposes into oxygen and water. No adverse effects.

3/23/2017 EN (English) SDS Ref: A124US 6/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR/RID/IMDG/IATA/ADN

Keep well ventilated and away from direct sunlight or heat sources.

14.1. UN number

Applies to PB007:

UN-No. : 2014 UN-No. (IATA) : 2014 UN-No. (IMDG) : 2014 UN-No. (ADN) : 2014

14.2. UN proper shipping name

Proper Shipping Name : HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Proper Shipping Name (IATA) : HYDROGEN PEROXIDE, AQUEOUS SOLUTIONS, 59 %

Transport document description : UN 2014 HYDROGEN PEROXIDE, AQUEOUS SOLUTIONS 59% STABILIZED, 5.1 (8), II

14.3. Transport hazard class(es)

 Class (UN)
 : 5.1

 Classification code (UN)
 : OC1

 Class (IATA)
 : 5.1

 Class (IMDG)
 : 5.1

 Class (ADN)
 : 5.1

 Hazard labels (UN)
 : 5.1, 8



14.4. Packing group

Packing group (UN) : II

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 58
Classification code (UN) : OC1

Orange plates :

58 2014

Transport category (ADR) : 2
Tunnel restriction code : E
Limited quantities (ADR) : 1L
Excepted quantities (ADR) : E2
EAC code : 2P

PB028: US and Canada: Ground Modes: Conforms with 49 CFR 173.4a and TDG 1.17.1

International: Ground Modes: Conforms with ADR/RID/ADG7 3.5

3/23/2017 EN (English) SDS Ref: A124US 7/8

Sterilant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6.2. Transport by sea

PB007: See above information (IMDG)

PB028: IMDG Conforms with IMDG 3.5 Shipping paper must state, "dangerous goods in excepted quantities"

14.6.3. Air transport

PB007: Forbidden (US, Canada, International)

PB028: Conforms with 49CFR SP A60 (US) Conforms with ICAO SP A75 (International)

14.6.4. Inland waterway transport

Vaprox HC is not considered a marine pollutant.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal Regulations

This product is regulated by the FDA as a medical device.

15.2. US State Regulations

Not applicable.

15.3. Canadian Regulations

The product is regulated by Health Canada as a drug.

SECTION 16: Other information

Revision Date : 3/23/17

Other information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and the Canadian Hazardous Products

Regulations (HPR).

Full text of H- phrases:

Acute Tox. 4 (Inhalation: mist)	Acute toxicity (Inhalation:mist), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (Oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Ox. Liq. 1	Oxidising Liquids, Category 1
Ox. Liq. 2	Oxidising Liquids, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
STOT SE 3	Specific target organ toxicity (single exposure), Category 3
H271	May cause fire or explosion; strong oxidiser
H272	May intensify fire; oxidiser
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H412	Harmful to aquatic life with long lasting effects

SDS GHS

The information on this sheet is not a specification and does not guarantee specific properties. The information is intended to provide general knowledge as to health and safety based upon our knowledge of the handling, storage and use of the product. It is not applicable to unusual or non-standard uses of the product or where instruction or recommendations are not followed.

3/23/2017 EN (English) SDS Ref: A124US 8/8